(19) World Intellectual Property Organization International Bureau



| 1970 | 1980 | 1 COLO COLO SER COLO COLO DE LA 10 DOMENTO ERO CORDO CORTO DEL COLO COLO COLO COLO COLO COLO C

(43) International Publication Date 2 June 2005 (02.06.2005)

PCT

(10) International Publication Number WO 2005/049958 A1

(51) International Patent Classification7:

E21B 21/00

(21) International Application Number:

PCT/NO2004/000353

(22) International Filing Date:

17 November 2004 (17.11.2004)

(25) Filing Language:

Norwegian

(26) Publication Language:

English

(30) Priority Data: 20035172

21 November 2003 (21.11.2003) NO

(71) Applicant (for all designated States except US): AGR SERVICES [NO/NO]; Lonavegen, Postboks 163, N-5342 Straume (NO).

(72) Inventor; and


(75) Inventor/Applicant (for US only): STAVE, Roger (NO/NO); Valahøgda 9, N-5355 Knarvik (NO).


(74) Agent: AS BERGEN PATENTKONTOR; Strandgaten 198, P.O. Box 1998 Nordnes, N-5817 Bergen (NO).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, BC, EB, BG, ES, FI, GB, GD, GB, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DB, DK, EB, ES, FL, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SB,

[Consinued on next page]

(54) Title: DEVICE FOR REMOVAL AND FILTRATION OF DRILLING FLUID





(57) Abstract: The invention relates to a device for removal and filtration of drilling fluid at top hole drilling, where a saction module (10) comprises an extended, pipe-formed body (30), open at the top and which is arranged to an ocean-bottom penetrating pipe, through which a drill stem is led for drilling of the top hole, and where the pipe-formed body (30) comprises at least one outlet passage (32) in the pipe wall for export of return drilling floid from the bore hole to a pump module (12). The invention is characterized in that the pipe-formed body (30) comprises a filtration device with through openings, where the mentioned openings are arranged to let through, to at least one outlet passage (32), return drilling fluid containing suspended material, such as swelling clay and stones, having a size that is less that the diameter of the inlet pipe of the pump or the openings of the pump.

BEST AVAILABLE COD